$\mathcal{U}$

UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/765,639	01/22/2001	Masahiro Maeda	Q62740	6818

			EXAMINER
23373	7590	06/03/2004	ROSALES HANNER, MORELLA I

SUGHRUE MION, PLLC
2100 PENNSYLVANIA AVENUE, N.W.
SUITE 800
WASHINGTON, DC 20037

ART UNIT	PAPER NUMBER
2128	

DATE MAILED: 06/03/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

PTO-90C (Rev. 10/03)

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE _3_ MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on _20 January 2000_.
2a) ☐ This action is **FINAL**.   2b) ☒ This action is non-final.
3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
  closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) _1-12_ is/are pending in the application.
  4a) Of the above claim(s) _____ is/are withdrawn from consideration.
5) ☐ Claim(s) _____ is/are allowed.
6) ☒ Claim(s) _1 - 12_ is/are rejected.
7) ☐ Claim(s) _____ is/are objected to.
8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.
10) ☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.
  Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
  Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
  a)☐ All   b)☐ Some *   c)☐ None of:
  1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. _____.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage
    application from the International Bureau (PCT Rule 17.2(a)).
  * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)
1) ☒ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
  Paper No(s)/Mail Date _____.
4) ☐ Interview Summary (PTO-413)
  Paper No(s)/Mail Date. _____.
5) ☐ Notice of Informal Patent Application (PTO-152)
6) ☐ Other: _____.

Detailed Action

1.   **Claims 1 – 12** are pending and have been examined.

Drawings

2.   **Figures 1, 2, 4A, 5, 6, 7, and 14** should be designated by a legend such as --

Prior Art-- because only that which is old is illustrated. See MPEP § 608.02(g). A

proposed drawing correction or corrected drawings are required in reply to the Office

action to avoid abandonment of the application. The objection to the drawings will not

be held in abeyance.

3.   **Figure 3** is objected to because it appears to contain misspelled words. For

example, elements 100, 102, 104 and 106c are labeled as "…CERATE…" instead of

"…CREATE…". A proposed drawing correction or corrected drawings are required in

reply to the Office action to avoid abandonment of the application. The objection to the

drawings will not be held in abeyance.

Priority

4.   The Office acknowledges applicant's claim for foreign priority under 35

U.S.C. 119(a)-(d). The certified copy has been filed in parent Application No. JAPAN

P2000-012054, filed on 01/20/2000.

Claim Interpretations

5.   Claims 1, 3, 6, 7, 8, 9 10, 11 and 12 recite the limitation '...imaginary light from

the light source...' this limitation has been interpreted as '...emitted light from the light

source...'.

Claim Rejections - 35 USC § 103

6.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in
> section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are
> such that the subject matter as a whole would have been obvious at the time the invention was made to a person
> having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the
> manner in which the invention was made.

6.1 Claims 1 – 12 are rejected under 35 U.S.C. 103 (a) as being clearly unpatentable

over **U.S. patent No. 5,836,668** issued to Ishikawa et al. hereafter referred to as

Ishikawa in view of a printed publication from Breault Research Organization titled

"Press Release Archive" hereafter referred to as *Breault* in further view of U.S. Patent

No. 5,675,495 issued to Biermann et al. hereafter referred to as *Biermann*.

6.1.1   As regard to **Claims 1 - 5, claim 1** is drawn to a method of evaluating

the reflection performance of a reflecting mirror designed for a vehicle lamp, comprising

the steps of:

    a.   Entering

- design information representing a plurality of reflecting basic surfaces

  which constitute the reflecting mirror and

- position information containing a light source position in the vehicle lamp;

  <u>and</u>

b.   displaying attribute information concerning an attribute

indicative of whether light from the light source position can effectively

reach each of a plurality of areas.

Ishikawa teaches [**Col. 2, lines 31 – 56**] a method of creating the

reflection surface of a reflection mirror of a vehicle lamp, comprising the steps

of:

a.   setting (entering): basic reflection surfaces, as curved

surfaces, based on restrictive conditions and a plural number

of paraboloids of revolution with different focal distances, but

disposed on a common axis and location of light source

located at a focal position; <u>and</u>

b.   specifying (displaying) the reflection surfaces having the best

incident angle distribution and setting it as the final reflection

surface.

Claim 2 is drawn to displaying attribute information concerning

the attribute with respect -to each of a plurality of areas into which each of the

remaining reflecting basic surfaces is divided on the basis of the design

information (**step c**).

Ishikawa teaches [**Col 2, lines 48 – 56**] calculating angles at which

light, emitted from the light source at the focal position, is incident (can

effectively reach) on different positions (plurality of areas) on each of the

candidate reflection surfaces under design consideration (based on the

restrictive body conditions as well as the distribution of angles at which light is

incident on the reflection surface).

Claim 3 is drawn to:

- generating divided area information so as to be associated with the
  design information, the divided area information being indicative of a
  plurality of areas, one reflecting basic surface selected from among
  the plurality of reflecting basic surfaces is divided into the plurality of
  areas on the basis of the design information (**Step d**);

- determining, on the basis of the divided area information and the design
  information, as to whether emitted light from the light source position can
  effectively reach each of the plurality of areas of the selected reflecting basic
  surface (**step e**) ; <u>and</u>

- generating attribute information concerning the attribute assigned to each of the
  plurality of areas on the basis of the determination, the attribute information
  being associated with at least one of the design information and the divided
  area information (**step f**).

Claim 4 is drawn to sequentially repeating **steps d, e and f** to each of the
remaining reflecting basic surfaces and displaying attribute information concerning the
attribute with respect to each of the plurality of areas into which each of the remaining
reflecting basic surfaces is divided on the basis of the design information.

Ishikawa teaches [**Col 3, lines 35 - 47**] the steps of:

- dividing (generating) each candidate basic reflection surface, under different
  setting (design) conditions, into different positions (plurality of areas);

- calculating (determining)angles at which light that is emitted from a light source located at the focal position is incident on the different positions (areas) of each of the basic reflection surfaces under the different settings (design conditions), and evaluating a distribution of the incident angles on each of the candidate basic reflection surfaces; and

- specifying (generating) the candidate basic reflection surface having the best incident angle distribution (attribute information) and setting it as the final basic reflection surface.

Ishikawa further teaches [**Fig 4B and accompanied text**] repeating the above steps for each of a plurality of basic reflection surfaces until the evaluation result reaches a preset evaluation level.

Claim 5 is drawn to a method according to claim 2, wherein the step (c) includes the steps of:

- providing an evaluation point to each of the plurality of areas;
- generating a straight line, the straight line connecting the evaluation point to the light source position; and
- making determination as to whether the straight line intersects a reflecting basic surface other than the reflecting basic surface which is associated with the plurality of areas.

Ishikawa teaches [**Fig 1 and accompanied text**]:

- providing an evaluation point (point F) to each of the plurality of areas;

- generating a straight line (line A) that connects the evaluation point to the

  position of the light source; and

- judging (making determination) that the incident angle distribution is good "when

  there are only the contours of equal incident angles that are smaller than a

  critical incident angle", which is allowable in securing the visual perception of the

  lamp within the reflection surface area.

Ishikawa does not expressly teach using this method for evaluating the

reflection performance of a reflecting mirror designed for a vehicle lamp.

Breault teaches [**Extensive New Feature Set Unveiled in ASAP 6.6 press release**]

ASAP, a professional optical modeling program designed to calculate the performance

of fully three-dimensional optical systems that allows engineers to test their optical

system by seeing what happens as light moves through the system. ASAP is designed

to meet the challenges of virtually any imaging or illumination application. Engineers use

ASAP in a wide range of industries including illumination and automotive. Using ASAP

enables designers to reduce product-to-market time by simulating optical systems prior

to prototyping and manufacturing. *Breault* discloses [**ASAP Module Predicts Illumination**

System Compliance press release] features in the ASAP 6.5 optical modeling program

that improve ray trace efficiency and allow the user to model coatings without

knowledge of the coating prescription with options in the Display-data Viewer that give

the user control over contours, palettes, cursors, and labeling while advanced control

options mean many more ways to view and analyze data. And enhancements to the

Builder make it even easier to use.

Biermann teaches [**Col. 1, lines 24 - 32**] that styling and performance

requirements now often demand automotive lamps with clear cover glasses. In these

lamps, the reflector is the only element used to control the output light distribution and

that these lamps may be designed with clear lenses by implementing Free-Form

Reflectors (FFR) into the lamp system. A FFK contains mathematically-computed

reflector surface that achieve the desired light distribution (also referred to as beam

pattern or photometric result) with or without refracting optical elements in front of

them. *Biermann* further teaches [**Col. 1, lines 32 - 36**] that there is a high demand for

lamps utilizing FFRs as well as a high demand for reducing design lead-time have

created a heavy dependence on lighting design and analysis tools.

Therefore, it would have been obvious to one of ordinary skills

in the art, at the time of the invention, to modify the method of creating

reflection surface of a reflection mirror of a vehicle lamp as taught by *Ishikawa*

to be used to evaluate the reflection performance of a reflecting surface

(mirror) as taught by *Breault* in order to reduce design lead-time as taught by

Biermann.

6.1.2   As regards to **Claims 6 - 12, claim 6** is drawn to a system for

evaluating reflection performance of a reflecting mirror designed for a vehicle lamp,

comprising:

- a memory;

- a display device to display:
- input means for entering design information and position information on a light source position in the vehicle lamp to store the entered information in the memory, the design information being indicative of a plurality of reflecting basic surfaces which constitute the reflecting mirror; and
- first transmitting means for transmitting, to the display device, attribute information concerning an attribute indicative of whether the emitted light from the light source position can effectively reach each of a plurality of areas, one reflecting basic surface selected from among the reflecting basic surfaces is divided into the plurality of areas on the basis of the design information.

Claim 7 is drawn to second transmitting means for transmitting attribute information concerning an attribute indicative of whether the emitted light from the light source position can effectively reach each of the plurality of areas, each of the remaining reflecting basic surfaces is divided into the plurality of areas on the basis of the design information.

Ishikawa teaches [**Col 3, lines 23 - 27**] that the evaluation of the incident angle distribution may be made automatically by processing the calculated values of the incident angles or the contours of equal incident angles by a computer and that [**Col 7, line 65 – Col 8, line 2**] the process described in Figs. 3 & 4B may be converted into storable and computer processable form, as would be understood by one of ordinary skill in the art, and that form may be stored on a readable medium, such as a floppy disk, ROM, RAM or the like. *Ishikawa* further teaches [**Fig 4A and accompanied text**] a block illustration of a basic processing system comprising a CPU which has access to a memory for storing data or programs as well as conventional sources of data and

programs, such as a keyboard or floppy disk, via an I/O port. The CPU may have a

counter for purposes to be explained and may be connected to a display for providing

an operator with information that enables interactive operations.

Claim 8 is drawn to an evaluation system comprising:

- means for generating divided area information;
- means for making determination, on the basis of the divided area information
  and the design information, as to whether the emitted light from the light source
  position can effectively reach each area of the selected reflecting basic
  surface; and
- first attribute means for generating, on the basis of the determination, attribute
  information concerning the attribute assigned to each of the plurality of areas,
  the attribute information being associated with at least one of the design
  information and the divided area information.

Ishikawa teaches [**Col 7, line 65 – Col 8, line 2**] the process described in Figs.
3 & 4B may be converted into storable and computer processable form, as would be
understood by one of ordinary skill in the art, and that form may be stored on a
readable medium, such as a floppy disk, ROM, RAM or the like.

Claim 9 is drawn to a computer-readable storage medium storing a
program to be executed by a computer, the program enabling thecomputer to evaluate
reflection performance of a reflecting mirror designed for a vehicle lamp, wherein the
program includes:

- an input process provided so as to enter design information and position
  information of a light source position in the vehicle lamp, the design information

being representative of a plurality of reflecting basic surfaces, the plurality of reflecting basic surfaces constituting the reflecting mirror; and

- a first display process provided so as to display attribute information concerning an attribute indicative of whether the emitted Light fromthe light source position can effectively reach each of a plurality of areas, one reflecting basic surface selected from among the plurality of reflecting basic surfaces is divided into the plurality of areas on the basis of the design information.

Claim 10 is drawn to the storage medium according to claim 9 wherein the program further comprises a second process provided so as to display attribute information concerning an attribute indicative of whether emitted light from the light source position can effectively reach each of a plurality of areas, each of the remaining reflecting basic surfaces is divided into the plurality of areas on the basis of the design information.

Ishikawa teaches [**Col 7, line 65 – Col 8, line 2**] the process described in Figs. 3 & 4B may be converted into storable and computer processable form, as would be understood by one of ordinary skill in the art, and that form may be stored on a readable medium, such as a floppy disk, ROM, RAM or the like.

Claim 11 is drawn to the storage medium according to claim 9, wherein the program further includes:

- a first division process provided so as to generate divided area information, the divided area information including area data on a plurality of areas into which one reflecting basic surface selected from among the reflecting basic surfaces is divided on the basis of the design information, the divided area information being associated with the design information;

- a first determination process provided so as to make determination, on the basis of the divided area information and the design information, as to whether the emitted light from the light source position can effectively reach each area of the selected reflecting basic surface; and

- a first attribute process provided so as to generate attribute information concerning the attribute assigned to each of the plurality of a reason the basis of the determination, the attribute information being associated with at least one of: the design information and the divided area information.

Claim 12 is drawn to executing the above processes a second time and to a third display process provided so as to display the attribute information concerning the attribute with respect to each of the plurality of areas into which each of the remaining reflecting basic surfaces is divided on the basis of the design information.

Ishikawa teaches [**Col 3, lines 35 - 47**] a method, of forming a reflection surface of a reflection mirror of a vehicle headlamp, comprising the steps of:

- dividing (generating) each candidate basic reflection surface, under different setting (design) conditions, into different positions (plurality of areas);

- calculating (determining)angles at which light that is emitted from a light source located at the focal position is incident on the different positions (areas) of each of the basic reflection surfaces under the different settings (design conditions), and evaluating a distribution of the incident angles on each of the candidate basic reflection surfaces; and

- specifying (generating) the candidate basic reflection surface having the best

  incident angle distribution (attribute information) and setting it as the final basic

  reflection surface.

Ishikawa also teaches [**Fig 4B and accompanied text**] repeating the above steps for each of a plurality of basic reflection surfaces until the evaluation result reaches a preset evaluation level.

Ishikawa further teaches [**Col 7, line 65 – Col 8, line 2**] that this method may be converted into storable and computer processable form, as would be understood by one of ordinary skill in the art, and that form may be stored on a readable medium, such as a floppy disk, ROM, RAM or the like.

Ishikawa does not expressly teach a system for evaluating the reflection performance of a reflecting mirror designed for a vehicle lamp.

Breault teaches [**Extensive New Feature Set Unveiled in ASAP 6.6 press release**] ASAP, a professional optical modeling program designed to calculate the performance of fully three-dimensional optical systems that allows engineers to test their optical system by seeing what happens as light moves through the system. ASAP is designed to meet the challenges of virtually any imaging or illumination application. Engineers use ASAP in a wide range of industries including illumination and automotive. Using ASAP enables designers to reduce product-to-market time by simulating optical systems prior to prototyping and manufacturing. *Breault* discloses [**ASAP Module Predicts Illumination System Compliance press release**] features in the ASAP 6.5 optical modeling program that improve ray trace efficiency and allow the user to model coatings

without knowledge of the coating prescription with options in the Display-data Viewer that give the user control over contours, palettes, cursors, and labeling while advanced control options mean many more ways to view and analyze data. And enhancements to the Builder make it even easier to use.

Biermann teaches [Col 1, lines 13 - 50] that computer assisted design of optical elements is well known in the art and that various computer programs for this purpose are known, these programs typically calculate images or light patterns for optical elements that are mathematically defined; a known technique for such calculation is ray tracing; in accordance with this technique, a program assumes various input light rays, calculates the effect of the optical element on the rays, and displays the resulting light pattern; such a program allows an optical designer to optimize the shape or other optical parameters of the element prior to manufacture of a prototype element.

Therefore, it would have been obvious to one of ordinary skills in the art, at the time of the invention, to modify the method, converted into storable and computer processable form, of creating reflection surface of a reflection mirror of a vehicle lamp and implemented as taught by *Ishikawa* to be used as a system for evaluating the reflection performance of a reflecting surface (mirror) as taught by *Breault* in order allows an optical designer to optimize the shape or other optical parameters of the element prior to manufacture of a prototype element as taught by *Biermann.*

Additional Information

7.   Any inquiry concerning this communication or earlier communication from the

examiner should be directed to Morella Rosales-Hanner whose telephone number is

(703) 305-8883. The examiner can normally be reached Monday-Friday from 7:00 a.m.

to 3:30 p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Kevin Teska can be reached on 703 305-9704. The fax number for the

organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or

proceeding should be directed to the receptionist whose telephone number is (703) 305-

3900.

MRH

May. 28, 2004